

HOF Hydraulic is a pioneer in the hydraulic industry and a leading exporter of hydraulic components in the world market. The company offers hydraulic vane pumps and other hydraulic components with a wide range of specification for new and after markets. HOF products have achieved top quality standards as a result of its commitment to continuous development of the design and features, the accuracy in material selection, a detailed production process and rigorous tests on every manufactured part.

Trinity Hydraulics represents HOF Hydraulic vane pumps, vane motors, cartridge kits, directional control valves, relief valves, tank accessories and other hydraulic components in the Middle East region.

vane pumps



pump type	vane pump fixed displacement
displacement range	7 - 193 cc
max operating pressure range	138 - 240 bar
mounting	face mounting flange

vane motors



motor type	vane motor
torque range	3.3 - 20.9 Nm/6, 9 bar
displacement range	29 - 193.2 cc

solenoid operated DCV - valve



valve	solenoid operated DCV
range	cetop 3 & cetop 5

pilot operated relief - valve



valve	pilot operated relief
size	3/8" to 1-1/4"
pressure	7 - 210 bar
flow	80 - 454 lpm

HOF Hydraulic is a pioneer in the hydraulic industry and a leading exporter of hydraulic components in the world market. The company offers hydraulic vane pumps and other hydraulic components with a wide range of specification for new and after markets. HOF products have achieved top quality standards as a result of its commitment to continuous development of the design and features, the accuracy in material selection, a detailed production process and rigorous tests on every manufactured part.

Trinity Hydraulics represents HOF Hydraulic vane pumps, vane motors, cartridge kits, directional control valves, relief valves, tank accessories and other hydraulic components in the Middle East region.

vane pumps



pump type	vane pump fixed displacement
displacement range	7 - 193 cc
max operating pressure range	138 - 240 bar
mounting	face mounting flange

vane motors



motor type	vane motor
torque range	3.3 - 20.9 Nm/6, 9 bar
displacement range	29 - 193.2 cc

solenoid operated DCV - valve



valve	solenoid operated DCV
range	cetop 3 & cetop 5

pilot operated relief - valve



valve	pilot operated relief
size	3/8" to 1-1/4"
pressure	7 - 210 bar
flow	80 - 454 lpm